

Republic of the Philippines
Department of Agriculture

AGRICULTURAL TRAINING INSTITUTE

ATI Building, Elliptical Road, Diliman, Quezon City, Metro Manila 1100

Tel. Nos. (63-2) 8929-8541 to 49 & 8928-7397 Fax No. (63-2) 8920-9792

Email: ati_director@ati.da.gov.ph & ati_director@yahoo.com

URL: http://www.ati.da.gov.ph; www.e-extension.gov.ph

REQUEST FOR QUOTATION

DATE: 07/18/2023

PURCHASE REQUEST NO.: PAD (BPP) FUND 2023-07-50

CANVASS NO. CO

Gentlemen:

Please quote your lowest price, taxes included, and subject to the terms and conditions that you may encounter purposely for article (s) and/or service(s) enumerated below, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than _____ in the return envelope attached here with.

Very truly yours:

NO.	QTY	UNIT	ITEM AND DESCRIPTION	UNIT PRICE	TOTAL
	2	unit	Laptop Computer (Executive with UNIX Based Operating System)	PRICE	
			Operating System: MacOS		
			Chip: M2 chip		
			8-core CPU with 4 performance cores and 4 efficiency cores; 10-core GPU;		
			16-core Neural Engine; 100GB/s memory bandwidth		
			Media engine: Hardware-accelerated H.264, HEVC, ProRes, and ProRes		
			RAW; Video decode engine; Video encode engine; ProRes encode and		
			decode engine		
			Display: Retina display; 13.3-inch (diagonal) LED-backlit display with IPS		
			technology; 2560-by-1600 native resolution at 227 pixels per inch with		
			support for millions of colors		
			500 nits brightness; Wide color (P3); True Tone technology		
			Battery and Power: Up to 20 hours TV app movie playback; Up to 17 hours		
			wireless web; 58.2-watt-hour lithium-polymer battery; 67W USB-C Power		
			Adapter		
			Memory: 8GB unified memory		
	1		Storage: 256 GB		
			Charging and Expansion; Two Thunderbolt / USB 4 ports with support		
			for: Charging, Display Port, Thunderbolt 3 (up to 40 Gbps), USB 4 (up to 40		
	1		Gbps), USB 3.1 Gen 2 (up to 10 Gbps)		
			Keyboard and Trackpad: Backlit Magic Keyboard with 65 (U.S.) or 66		
			(ISO) keys including 4 arrow keys in an inverted T arrangement, Touch Bar.		
			Touch ID, Ambient light sensor, Force Touch trackpad for precise cursor		
			control and pressure sensing capabilities; enables Force clicks, accelerators,		
			pressure sensitive drawing, and Multi Touch gestures		
			Wireless: Wi-Fi - 802.11ax Wi-Fi 6 wireless networking, IEEE		
			802.11a/b/g/n/ac compatible		
			Bluetooth: Bluetooth 5.0 wireless technology		
			Camera: 720p FaceTime HD camera; Advanced image signal processor with		
			computational video		
			Size and Weight:		
			• Height: 1.56cm		
			• Width: 30.41cm		
			• Depth: 21.24cm		
			• Weight: 1.38kg		
			Warranty: At least 1 year		
			Color: Silver or Space Gray		
			Inclusion: MS Office for Mac Bundle		
	1	unit	Videoconferencing Camera, Microphone, and Speaker		
			Camera		
			Height: 182.5 mm; Width: 152 mm; Depth: 152 mm		
			Speaker		
			Height: 103 mm; Width: 449 mm; Depth: 80 mm		
			Mic Pod		
			Height: 21 mm; Width 102 mm; Depth: 102 mm		
			Lighting		
			Low-light compensation		
			Video noise reduction		
			Low-light saturation optimization		
			Renders natural skin tones for each participant on camera		
			Reduces backlighting and glare without darkening the entire image.		
			reduces packlighting and glare without darkening the entire image	- 1	

NO.	31	QTY *	UNIT	ITEM AND DESCRIPTION	UNIT PRICE	TOTAL
				Sight		
				Human figure detection		
				Auto-frame participants at meeting start Auto-frame participants on-demand		
				Auto-reframe participants during meetings		
				Sound		
				Machine learning AI trained to distinguish human speech from other sounds		
				AEC (Acoustic Echo Cancellation) VAD (Voice Activity Detector)		
				Background noise suppression		
				Auto-level loud and soft voices		
				Mic Matrix		
				Very low distortion broadside beamforming algorithm steers the factory- paired microphones directly at the talker for the best voice pickup and		
				noise reduction Supports up to 56 acoustic beams (8 per Rally Mic Pod) to lock onto the		
				active talker Beam focus refresh rate: 8ms (125 times/second)		
				Anti-Vibration Suspension		
				A patent-pending suspension system decouples the speaker module within		
				the external enclosure, virtually eliminating the vibrations that can travel through walls, stands, and tables. This improves the echo cancelling performance of Rally Mic Pods, while ensuring that video images remain		
				clear and steady, even at high volume levels and when zoomed in.		
				Peak-limiting algorithm eliminates even momentary speaker clipping to prevent distortion		
				Camera Zoom: 15v UD zoom (5v optical + 2v digital)		
				Zoom: 15x HD zoom (5x optical + 3x digital) Pan: 180° (±90°)		
				Tilt: 140° (+50° / -90°)		
				Field of View		
	İ			Diagonal: 90°		
				Horizontal: 82°		
				Vertical: 52°		
	Ì			Total Room Coverage: 262° wide x 192° tall (field of view + pan and tilt)		
				Resolutions @ 30fps: 4K Ultra HD, 1440p, 1080p, 900p, 720p, and SD		
				Resolutions @ 60fps: 1080p, 720p		
				RightLight Technologies: Wide Dynamic Range (WDR), low-light compensation, video noise reduction, low-light saturation optimization		
				Privacy: Lens parks at -90° in sleep mode for assured privacy Mic Pod		
				Pickup Range: 7 m diameter		
				Four omnidirectional microphones forming eight acoustic beams		
				AEC: Acoustic Echo Cancellation		
				VAD: Voice Activity Detector		
				Background noise suppression		
				Mute button with LED status indicator		
				Captive 2.95 m 12-pin cable		
				Daisy chain up to 7 Rally Mic Pods		
			1	Frequency Response: 90Hz – 16kHz Sensitivity: >-27 dB +/-1dB @ 1Pa		
			1	Microphone data rate: 48 kHz		
				Recommended # of participants		
				Rally (one Mic Pod): 16		
				Rally Plus (two Mic Pods): 16		
			1	Additional participants per Mic Pod: 6		
				Recommended participants for Rally with 7 Mic Pods: 46 Speaker		
				High-performance 76 mm driver with rare-earth magnet		
				Patent-pending suspension system eliminates vibration-induced camera shake and audio interference		
				Mini XLR cable connects to Rally Display Hub for both signal and power Speaker volume 95dB SPL @1W, 100dB SPL @7.5W, both +/-2dB at ½		
				meter Sensitivity: 95+/-2 dB SPL at ½ meter		
				Distortion: 200Hz-300Hz <2.5%, 300Hz-10kHz < 1%@7.5W		
				Sampling rate: 48 kHz		
				Table Hub Single CAT6A cable connection to Rally Display Hub 5 m cable included,		
				supports customer-supplied cables up to 50 m Hub 5 m cable included, supports customer-supplied cables up to 50 m		
				Active speaker detection: analyzes audio from up to 7 Mic Pods and 56 beams every 8 ms		

NO.	" QTY "	UNIT	ITEM AND DESCRIPTION	PRICE	TOTAL
¥'1	*		12 Pin connector for Rally Mic Pod	FRICE	
			HDMI Type A passthrough to Display Hub (x2)		
			USB Type C		
			USB Type A (reserved for future capability)		
			USB Type B (connects to meeting room computer)		
			RJ45 (reserved for future capability)		
			Power input		
			Display Hub		
			HDMI Type A: (x2) (connects to displays)		
			USB C (connects to Rally Camera)		
			USB Type B (connects to meeting room computer)		
			RJ45: connects to Table Hub		
			Mini XLR: x2		
			Powers one or two Rally Speakers		
			Power input		
			Remote Control		
			RF remote control (line of sight not required)		
			CR2032 batteries (included)		
			Cables / Power		
			Camera to Display Hub		
			2 m USB 3.1 Type C to USB Type C 3.1		
			Conference Room Computer to Display or Table Hub		
			2 m USB 3.1 Type A to USB Type B		
			Display Hub to Table Hub		
			5 m CAT6A Ethernet cable (supports customer-supplied cables up to 50 m		
	l l		Display Hub to Speaker (x2)		
			2.95 m Mini XLR (supports customer-supplied extension cables up to 3 m		
			Conference Room Computer to Displays (x2)		
			2 m HDMI A		
			Mic Pod		
			2.95 m: Hardwired with 12 pin connector		
			Power Outlets to Power Supplies (x2): 1 m		
			1 m		
			Power Supplies to Table Hub / Display Hub (x2)		
			1.5 m		
	l,		Certifications		
			Certified for Skype for Business and ready for Teams		
			Zoom Certified		
			Certified for Google Hangouts Meet Hardware		
			Microsoft Cortana® certified		
			Cisco Jabber and WebEx compatible		
			Compatible with BlueJeans, BroadSoft, Video, and other video conferencing,		
			recording, and broadcasting applications that support USB cameras		
			Compatibility		
			Plug-and-play USB connectivity		
			Appliance Mode		
			Supports compatible video conferencing software in appliance mode when		
			deployed with Logitech RoomMate, including Zoom Rooms Appliances. Certification pending for Microsoft Teams Rooms on Android and additional		
			video conferencing platforms.		
			Warranty: 2-Year Limited Hardware Warranty		
PURPOS			That railey 12 fear binneed flat dware warranty		
		ze researc	ch and production of various multi-media materials, database managen	ont and co	nduct of wintual
activitie	s under the Bi	nhi ng Pa	g-asa Program (BPP).	ient, and co	ilduct of virtual
Pls. sub	mit the followi	ng eligibi	lity documents:		
May	or's/Business	Permit	IN ■ CONTRACTOR CONTRACTOR AND		
Inco	me Tax Retur	n			
Not	arized Omnibu	ıs Sworn	Statement		
Phil	GEPS Registra	tion Num	ber/Red Membership		
	tificate of Sole				
			·		
Note: Pl	s. provide also	the follow	wing: contact information such as email address and mobile/landline n	umbers: Ta:	x Identification
Number	and Bank Deta	ails			
I hereby	certify that I a	am in the	position to furnish the above article(s), service(s) at the prices and in c	uantities as	
called fo	r except as I h	ave indica	ated. The articles are available in our stock for immediate delivery to the	e Agricultu	ral
Training	g Institute, Elli	ptical Roa	id, Diliman, Quezon City	untu	
	-	and the second of the second o			
MODEL:					
DELIVE	RY PERIOD:				
	NTY PERIOD: _				
	ALIDITY:		Signature Over printed name of proprietor/	Manager	
			or Authorized Representative	_	
CANVAS	SED BY:				
DATE:					

page 3 of 3